Kundeninformation Customer information



| An / To: | Kunde / Customer | Zur Info an: For Info to: | V,TACAD, GF |
|----------------------|---|------------------------------|----------------|
| Von / From: | AL | Datum / Date: | 20.05.15 |
| Betreff: Subject: | The successor product "F30 control cabinet" | · | |

The successor product of the "F30 control cabinet" is the result of diverse standard modifications. It has been specially adapted for MRL use.

The "F30 standing cabinet" with NEW *LIFT* article number 57-03021 is replaced by the successor product "standing cabinet E/F/I 30" with NEW *LIFT* article number 57-03051 (DIN right) / 52 (DIN left). The predecessor product is still available on request.

Specific characteristics of the successor product "standing cabinet E/F/I 30":

- External dimensions: 2178 x 578 x 275mm (HxWxD) + socket 100x518x255 (HxWxD) heightadjustable with the leveling feet from 125 to 150mm.
- Fire load insulation 30 minutes →I30
- Colour similar to RAL 7035 (light grey)
- Fire resistance 30 minutes →F30
- Functional integrity 30 minutes → E30
- IP54
- 2-point locking push rod swivelling lever with exchangeable DIN profile semi-cylinder, KABA and ASSA in preparation.
- HPL (High Pressure Laminate) surface (outside)

Please pay attention to the changed dimensions in comparison to the predecessor

Predecessor product: $H=2204 \times W=517 \times D=282 + \text{socket } 118-175 \text{mm}$ adjustable $H=2178 \times W=578 \times D=295 + \text{socket } 125-150 \text{mm}$ adjustable

For any further questions do not hesitate to contact us.

0049 89 89 866 - 0 0049 89 89 866 - 300 info@newlift.de

| Erstellt: | EP | Datum: | 10.01.2013 | Seite: 1 von 1 |
|------------|-----|---------|------------|--------------------------------|
| Geprüft: | QMB | Datum : | 10.01.2013 | FB Kundeninformation_DE_EN.doc |
| Genehmigt: | PZ | Datum : | 15.01.2013 | Stand 01/2013 |